

# Minimate Pro 6™

## Advanced Vibration, Air Overpressure and Sound Monitoring Using 6 Channels

With over 40 years of expertise, InstanTEL has set the industry standard with our vibration, air-overpressure, and sound monitoring units. Our monitoring units are used worldwide enforcing our reputation as a global leader of tough, rugged, and reliable products.

### Key Features

- 7,100+ events storage capacity. (28,000 with extended memory)
- Uninterrupted monitoring with zero dead-time between events.
- Records full waveform events up to 2.5 hours long. (triggered, 6-channel at 1024 SPS)
- Records full waveform events up to 19 hours long. (manual, 6-channel at 1024 SPS with extended memory)
- Histogram-Combo mode captures full-waveform events in parallel to Histogram recording.
- Synchronize event data to within 100 microseconds. (optional GPS required)
- EMI Shielding, Ethernet Connection and Waterproof rating of IP67.
- Internal battery lasting up to 10 days.

### Range of Applications

- Construction Activity
- Underwater Monitoring
- Demolitions
- Near/Far-Field Blast Analysis
- Heavy Transportation
- Pile Driving
- Vibration Dose Value (VDV)
- Research/Education
- Sound Monitoring

### Monitor Remote Locations

- Integrates seamlessly into THOR/Vision Event Management Software
- Auto Call Home relays your data straight to you or automatically posts the data to Vision

### Sensor Options (Compliance)

- ISEE Triaxial Geophone
- Triaxial Borehole Geophone
- ISEE Linear Microphone
- DIN Triaxial Geophone (1-80 Hz or 1-315 Hz)
- Sound Level Microphone

### Sensor Options (Requires THOR Advanced License)

- High-Frequency Geophones and Boreholes (30 - 1,000 Hz)
- High-Pressure Microphone (up to 10 psi)
- Hydrophone (8 - 500 Hz)
- Accelerometers (1 - 3,000 Hz for 0.5 g and 50 g, 0.5 - 500 Hz for 500 g)

### Enhance Your Data Analysis Using InstanTEL's THOR Advanced Software

- Reduce vibrations efficiently using the Signature Hole Analysis feature.
- Calculate the structural response based on a comparison of two waveforms recorded inside and simultaneously outside a structure.
- Calculate the effects of vibrations (Vibration Dose Value, VDV) with our Human Exposure Reports feature.

### THOR Includes the Following Compliance Standards and Graphs

- Australia 2187.2-1993
- Brazilian Standard NBR 9653/2005
- British Standard 7385
- BS 6472:1992 (Curves 8,16,20,32,60,90,128)
- Criterio Prevencion (Une 22.381)
- Czech and Slovak Standard
- DIN 4150
- DIN 45669-1 (2010)
- Function de Ponderation
- GFEE + Ministère Environnement
- Harmoniska Svängningar
- Indian CMRI, DGMS India (A) & (B)
- Indonesian SNI 7571:2010
- ISEE Seismograph Specification -2022
- New Zealand 4403:1976
- NOM-026-SESH-2007
- NZS/ISO 2631-2:1989 Combined curves
- QLD APP Standard
- Recommendation GFEE/GFEE\*
- Swiss SN 640 312a (Mining/Pile Driving/Traffic)
- Toronto 514-2008
- Turkey Mining & Quarry
- USBM RI8507 And OSMRE



ISEE Geophone with a Linear Microphone or Sound Level Microphone



Two Geophones



Available Compliance Sensors



Available Advanced Sensors

## General Specifications

<b>Minimate Pro Monitoring Unit Channels</b>	Channels 1-3, ISEE or DIN Triaxial Geophone or various configurations of advanced sensors. Channels 4-6, a 2nd ISEE / DIN Triaxial Geophone, or an ISEE Linear Microphone or Sound Level Microphone, or various configurations of advanced sensors.	
<b>Geophone</b>	<b>ISEE</b> Up to 254 mm/s (10 in/s) ISEE Seismograph Specification (2022) 0.00788 mm/s (0.00031 in/s) 2 to 250 Hz From 2 to 4 Hz and 125 to 250 Hz: +5% to -3 dB of an ideal flat response, from 4 to 125 Hz: $\pm 5\%$ or $\pm 0.5$ mm/s (0.02 in/s) whichever is larger. Phase shift from 2.5 to 250 Hz <10% of maximum absolute value of 2 superimposed harmonic vibrations. 2.2 g/cc (137 lbs/ft <sup>3</sup> ) 75 m (250 ft)	<b>DIN</b> Up to 254 mm/s (10 in/s) DIN 45669-1 0.00788 mm/s (0.00031 in/s) 1 to 315 Hz or 1 to 80 Hz DIN: 45669-1 standard
<b>Microphones</b>	<b>ISEE Linear Microphone</b> ISEE Linear Microphone ISEE Seismograph Specification (2022) Up to 500 Pa (0.0725 psi) [148 dB] 0.0156 Pa (2.2662x10 <sup>-6</sup> psi) 2 to 250 Hz 2 Hz: -3 dB $\pm 1$ dB, 3 Hz: -1 dB $\pm 1$ dB, from 4 Hz to 125 Hz: $\pm 1$ dB, 200 Hz: +1 dB to -3 dB, 250 Hz +1 dB to -4 dB 75 m (250 ft)	<b>Sound Level Microphone</b> A-Weight or C-Weight Fast (125ms) or Slow (1s) 30 to 140 dB A or C 0.05 dB (Display limit 0.1dB) Up to 20 kHz IEC 61672 Class 1 75 m (250 ft)
<b>Optional Advanced Sensors</b>	High Pressure Microphone, High Frequency Geophone, High Frequency Borehole Geophone, Uniaxial and Triaxial Accelerometers, Hydrophone (Please contact InstanTel for more information).	

## Waveform Recording

<b>Record Modes</b>	Waveform, Waveform Manual
<b>Seismic Trigger</b>	0.13 to 254 mm/s (0.005 to 10 in/s)
<b>Linear Acoustic Trigger</b>	2.0 to 500 Pa (0.00029 to 0.0725 psi) [100 to 148 dB]
<b>Sound Level Microphone Trigger</b>	33 to 140 dB (A or C)
<b>Sample Rate (per channel)</b>	512, 1,024, 2,048, 4,096, (with an advanced license: 8,192, 16,384, 32,768, 65,536) S/s (independent of record time)
<b>Record Stop Mode</b>	Fixed record time, AutoRecord™ (see Auto Record Time below)
<b>Record Time</b>	1-9,000 seconds (1-30 seconds, then 30-second increments up to 9,000 seconds) plus a 0.25 second pre-trigger.
<b>Auto Record Time</b>	Event is recorded until activity remains below trigger level for duration of auto window, or until available memory is full.
<b>Cycle Time</b>	Recording uninterrupted by event processing, monitoring, or communication - no dead time below 65 KHz.
<b>Storage Capacity</b>	64 MBs. Optional 240 MBs.
<b>Full Waveform Events</b>	7,100+ 1-second events at 1,024 S/s sample rate with two geophones (28,000 with extended memory)

## Histogram Recording

<b>Record Modes</b>	Histogram and Histogram Combo™ (unit captures triggered waveforms while recording in Histogram mode)
<b>Recording Interval</b>	2 seconds up to 30 seconds (1-second increments), 30 seconds up to 60 minutes (30-second increments)
<b>Histogram Storage Capacity</b>	512,000 intervals (Examples: ~12 days at 2-second intervals, ~1 year at 1-minute intervals with two geophones)
<b>Histogram Combo Storage Capacity</b>	30 days of Histogram recording at 1-minute intervals, and over 6,500 1-second waveform events at 1,024 S/s

## Physical Specifications

<b>Dimensions</b>	25.4(l) x 11.75(w) x 10.80(h) cm (10.00 x 4.63 x 4.25 in); length dimension includes connectors and dust caps
<b>Unit Weight</b>	2.27 kg (5 lbs)
<b>Battery</b>	10 Days
<b>User Interface</b>	10 domed tactile with separate keys for common functions
<b>Display</b>	7-line x 32-character, high-contrast, backlit LCD
<b>PC Interface</b>	Ethernet cable, supplied, for PC to unit connection or RS-232 with an optional USB adapter
<b>Auxiliary Inputs and Outputs</b>	External Trigger and Remote Alarm
<b>Environmental</b>	
<b>• LCD Operating Temperature</b>	-20 to 45 °C (-4 to 113 °F)
<b>• Electronics Operating Temperature</b>	-40 to 45 °C (-40 to 113 °F)
<b>• Water Resistance</b>	IP67 – submerge to 30 cm (1 ft) for 24 hours
<b>Remote Communications</b>	Supported modems: Sierra Wireless™ Airlink® RV-50, GX-400, LS-300. Automatically transfers events when they occur through the Auto Call Home feature, monitor start/stop timer.
<b>Optional Features</b>	
<b>• GPS</b>	Factory installed, for time synchronizing event data.
<b>• Vision (Cloud-based software)</b>	Provides stakeholders with secure, encrypted, access to event data, and allows instant sharing for time-sensitive projects.
<b>Electrical Standards</b>	CE Class B. The Minimate Pro monitoring unit has been tested and passed IEC 61010-1:(2nd ed. 2001) (CB scheme test report available).